



KMAT L HP

Year of last update: 2024

Function: Erosion control

STRUCTURE: three dimensional, high void ratio erosion prevention geomat obtained from extruded monofilaments tangled and welded where they cross.

PROPERTIES

			tol
Product		Geomat	
Raw material (+ UV stabilizer)		PP	
Void ratio	%	>95	±5%

PHYSICAL/ MECHANICAL CHARACTERISTICS

				tol
Thickness at 2 kPa	EN 9863-1	mm	16	±3
Tensile strength MD	EN ISO 10319	kN/m	>2	
Tensile strength CMD	EN ISO 10319	kN/m	>1	
Extension at max load MD	EN ISO 10319	%	>50	
Extension at max load CMD	EN ISO 10319	%	>50	

STANDARD DIMENSIONS

				tol
Width		m	2-4	-5%
Length		m	30	±5%

To be covered within one month after installation



The information given in this data sheet is to the best of our knowledge true and correct. TeMa srl reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

TeMa Technologies and Materials srl

Via dell'Industria 21 - 31029 Vittorio V.to (TV) Tel. +39.0438.50.31 - Fax +39.0438.50.34.60 - e-mail: info@temacorporation.com - www.temacorporation.com

REV. 1/2024