



KMAT MINI L GRASS

Year of last update: 2024

Function: Erosion control

STRUCTURE: three dimensional, high void ratio erosion prevention geomat obtained from extruded monofilaments tangled and welded where they cross, bonded to a biodegradable pre-seeded textile

PROPERTIES

tol

Product			Geomat	
Raw material (+ UV stabilizer)			PP	
Void ratio	%	>95		±5%

PROPERTIES OF SEEDED TEXTILE

tol

Textile raw material			Viscose	
Textile saturation material			Seeds, fertilizer, inerts	
Thickness at 2 kPa	EN ISO 9863	mm	3	±1
Tensile strenght MD	EN ISO 10319	kN/m	>0,6	
Extension at max load MD	EN ISO 10319	%	>40	

PHYSICAL/ MECHANICAL CHARACTERISTICS

tol

Thickness at 2 kPa	EN 9863-1	mm	10	±3
Tensile strength MD	EN ISO 10319	kN/m	>1,2	
Tensile strength CMD	EN ISO 10319	kN/m	>0,25	
Extension at max load MD	EN ISO 10319	%	>50	
Extension at max load CMD	EN ISO 10319	%	>50	

STANDARD DIMENSIONS

tol

Width		m	2-4	-5%
Length		m	75	±5%

To be covered within one month after installation



The information given in this data sheet is to the best of our knowledge true and correct. TeMa srl reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

TeMa Technologies and Materials srl

Via dell'Industria 21 - 31029 Vittorio V.to (TV) Tel. +39.0438.50.31 - Fax +39.0438.50.34.60 - e-mail: info@temacorporation.com - www.temacorporation.com

REV. 1/2024