



T-NET 5,2 65

Year of last update: 2024

STRUCTURE: HDPE geonet

GEONET

tol

Raw material (+ UV st.)			HDPE	
Thickness at 2 and 200 kPa	EN ISO 9863-1	mm	5,2/4,8	±20%
Weight	EN ISO 9864	g/m ²	650	±10%
Tensile strength MD	EN ISO 10319	kN/m	>4,5	
Elongation at max load MD	EN ISO 10319	%	40	±15%

HYDRAULIC PERFORMANCES

tol

Plane flow capacity MD, i=1, R/R	EN ISO 12958	l/(m·s)		±30%
	<i>Hydraulic gradient (*)</i>		<i>i = 1</i>	
	Load: 20 kPa		1,7	
	" 200 kPa		1,2	

S/S: Soft/Soft Contact - S/R: Soft/Rigid Contact - R/R: Rigid/Rigid Contact

STANDARD DIMENSIONS

tol

Width		m	1,9-3,8	±6%
Length		m	30	±3%

To be covered within one month after installation



The information given in this data sheet is to the best of our knowledge true and correct. TeMa srl reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

TeMa Technologies and Materials srl

Via dell'Industria 21 - 31029 Vittorio V.to (TV) Tel. +39.0438.50.31 - Fax +39.0438.50.34.60 - e-mail: info@temacorporation.com - www.temacorporation.com

REV. 1/2024